

# FullView®



Site Validation  
Analysis

PROJECT

Western Wind and Solar Integration Study  
Tower 06008

FOR

National Renewable Energy Laboratory

Copyright ©2009 3TIER, Inc.  
All rights reserved.

DATE

January 20, 2009

CONTACT

ph: 206.325.1573  
fax: 206.325.1618

[info@3tiergroup.com](mailto:info@3tiergroup.com)  
[www.3tiergroup.com](http://www.3tiergroup.com)

2001 Sixth Avenue, Suite 2100  
Seattle, WA 98121-2534







## 1 INTRODUCTION

---

3TIER has been retained by National Renewable Energy Laboratory (NREL) to assess the wind resource over the western region of the United States utilizing a numerical weather prediction (NWP) model. This report examines the quality of the NWP simulations used for that assessment at a single point within the study area. For this report, the observations were taken at Tower 06008 in Colorado (latitude 40.66617, longitude –103.3448).

The average observed wind speed (for all valid observational times) at 20 meters during the 17 months of the period of record (July, 2005 to November, 2006) is 5.29  $m/s$  with an hourly standard deviation of 3.39  $m/s$  at Tower 06008. This compares to a modeled 20m wind speed of 4.84  $m/s$  with a 2.71  $m/s$  standard deviation for these same times.

This report presents a comparison of the simulated winds with the observations at the reference tower. The focus of the verification is on the model's ability to reproduce the observed variability of the wind resource at daily and monthly time scales, while preserving the distribution of hourly wind speeds and the diurnal characteristics of the wind.



## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Model simulations by 3TIER</b>	<b>3</b>
<b>3</b>	<b>Validation of Model Results at Tower 06008</b>	<b>5</b>
3.1	Observational Data . . . . .	5
3.2	Model validation statistics . . . . .	5
3.3	Monthly-mean wind speed . . . . .	6
3.4	Wind speed distribution . . . . .	7
3.5	Wind direction distribution . . . . .	8
3.6	Diurnal variability of wind speed . . . . .	11
3.7	Tabular data . . . . .	13



## 2 MODEL SIMULATIONS BY 3TIER


The assessment of the wind resource across Western U.S. presented in this report is based on 17 months of simulated data (July, 2005 through November, 2006) using a regional nonhydrostatic primitive equation model of the atmosphere.

3TIER configured the NWP model using nested grids to simulate the wind resource over the Western U.S. region. Some details of the NWP configuration are shown below in Table 1. The extent of the coarsest grid was selected to capture the effect of synoptic weather events on the wind resource at the site, as well as to allow the model to develop regional, thermally-driven circulations. The increasingly fine 54km, 18km, 6km and 2km grids were selected to model the effect of local terrain and local scale atmospheric circulations. A map of the meteorological towers used to validate the model simulations is shown in Figure 1.

A detailed discussion of the model's ability to recreate the observed winds at Tower 06008 is contained in Section 3.

Parameter	Value
Mesoscale numerical weather prediction model	WRF
Horizontal resolution of valid study area	2km
Number of vertical levels	37
Elevation data base	3 second SRTM
Vegetation data base	30 second USGS
Soil classification	30 second USGS
Surface parameterization	Monin-Obukhov similarity model
Boundary layer parameterization	YSU model (MRF with entrainment)
Land surface scheme	5-layer soil diffusivity model

**Table 1:** Numerical weather prediction model configuration



**Figure 1:** Meteorological towers used to validate the Western Wind and Solar Integration Study simulations are shown as yellow dots.



## 3 VALIDATION OF MODEL RESULTS AT TOWER 06008

### 3.1 Observational Data

Approximately 17 months of data (July, 2005 to November, 2006) from a 20m meteorological tower (Tower 06008) at Western U.S. were used in this analysis. This tower will be referred to as the reference tower throughout this report. The data at 20m were used to assess the quality of the model simulations at 20m.

The observed and modeled wind speeds shown in this section represent the mean of all times during the month for which a valid wind speed observation was available. Therefore they should not be interpreted as estimates of the true wind speeds at the site, but rather a verification of the model's ability to reproduce the available observed wind speeds. Any month or hour missing greater than 50% of the available observations is omitted from the following figures, tables, and statistics.

It should be noted that meteorological observations provided to 3TIER are not allowed to influence the raw model simulations.

### 3.2 Model validation statistics


Table 2 presents some basic statistical measures of the model performance relative to the measured winds at the reference tower during the observational period. For reference, the correlation ( $r$ ) of the reference tower data to itself is perfect and hence the explained variance ( $r^2$ ) value is 1.0.

Comparison	Value
Correlation of monthly-mean simulated wind speed to observed	0.94
RMS error of monthly-mean simulated wind speed	0.50 m/s
Correlation of daily-mean simulated wind speed to observed	0.74
RMS error of daily-mean simulated wind speed	1.57 m/s

**Table 2:** Correlation ( $r$ ) and root mean square (RMS) error statistics of modeled wind speeds.




### 3.3 Monthly-mean wind speed



**Figure 2:** A comparison of the observed and simulated monthly-mean 20m wind speed at Tower 06008. Explained variance ( $r^2$ ) value of each data source relative to the monthly reference tower wind speeds are shown in the legend. Months missing greater than 50% of the available observations are not plotted. Tabular formatted data are available in Table 3 (p. 13).




### 3.4 Wind speed distribution



**Figure 3:** A comparison of the observed and simulated hourly wind speed distributions at 20m at Tower 06008 during the period of record, using 1 m/s bins. (0 m/s bin contains only values  $\leq 0.5$ ) Fitted Weibull distributions are also displayed with the scale( $A$ ) and shape( $k$ ) parameters listed in the legend. Tabular formatted data are available in Tables 6 and 7 (p. 16 and 17).



### 3.5 Wind direction distribution




**Figure 4:** Wind roses at Tower 06008 for observations and simulated model output for the period of record (July, 2005–November, 2006). Directional bins are  $22.5^\circ$  wide, and the radial contour interval is 10%. Tabular formatted data, including mean wind speed values and Weibull parameters for each wind direction sector, are available in Tables 8 and 9 (p. 18 and 19).




Validation

Tower 06008

Western Wind and Solar Integration Study  
For National Renewable Energy Laboratory


**Figure 5:** Wind rose of observed wind direction at Tower 06008 for each month. Directional bins are  $22.5^\circ$  wide, and the radial contour interval is 0.1, i.e. 10%.



**Figure 6:** Wind rose of simulated wind direction at Tower 06008 for each month. Directional bins are  $22.5^\circ$  wide, and the radial contour interval is 0.1, i.e. 10%.




### 3.6 Diurnal variability of wind speed



**Figure 7:** A comparison of the diurnal cycle of observed and simulated 20m wind speed at Tower 06008. Data are averaged over the period of record (July, 2005–November, 2006). Hours missing greater than 50% of the available observations are not plotted. Tabular formatted data are available in Tables 4 and 5 (p. 14 and 15).

Time Zone	UTC Offset	24-hour Time					
		14:00 Sun	20:00 Sun	02:00 Mon	08:00 Mon	13:00 Mon	
Hawaii	-10:00						
US Pacific	-08:00	16:00 Sun	22:00 Sun	04:00 Mon	10:00 Mon	15:00 Mon	
US Eastern	-05:00	19:00 Sun	01:00 Mon	07:00 Mon	13:00 Mon	18:00 Mon	
Brazil Eastern	-03:00	21:00 Sun	03:00 Mon	09:00 Mon	15:00 Mon	20:00 Mon	
<b>UTC/GMT</b>	<b>±00:00</b>	<b>00:00 Mon</b>	<b>06:00 Mon</b>	<b>12:00 Mon</b>	<b>18:00 Mon</b>	<b>23:00 Mon</b>	
Central European	+01:00	01:00 Mon	07:00 Mon	13:00 Mon	19:00 Mon	00:00 Tues	
India	+05:30	05:30 Mon	11:30 Mon	17:30 Mon	23:30 Mon	04:30 Tues	
China	+08:00	08:00 Mon	14:00 Mon	20:00 Mon	02:00 Tues	07:00 Tues	
Australia Eastern	+10:00	10:00 Mon	16:00 Mon	22:00 Mon	04:00 Tues	09:00 Tues	

All times in this report are in Coordinated Universal Standard Time (UTC), also known as Greenwich Mean Time (GMT). This table can be used to convert from UTC to Local Standard Time for the time zones listed above. To change to Daylight Savings Time, add +1 hour. For example, at 00:00 UTC on Monday, the local standard time in the US Eastern time zone is 19:00 on Sunday.



**Figure 8:** A comparison of the diurnal cycle of observed and simulated 20m wind speed for each month at Tower 06008. Hours missing greater than 50% of the available observations are not plotted. Tabular formatted data are available in Tables 4 and 5 (p. 14 and 15).



### 3.7 Tabular data

Month	Observed	Simulated	Bias	Availability(%)
07/2005	4.70	4.44	-0.27	74.9
08/2005	4.43	4.21	-0.22	98.7
09/2005	4.29	3.94	-0.34	98.8
10/2005	4.56	4.10	-0.46	97.8
11/2005	6.54	5.87	-0.67	98.6
12/2005	5.46	5.47	0.01	99.3
01/2006	5.76	5.50	-0.26	99.3
02/2006	6.05	5.64	-0.41	98.5
03/2006	5.77	5.33	-0.45	98.9
04/2006	6.62	5.60	-1.02	99.2
05/2006	5.43	4.85	-0.58	87.1
06/2006	4.97	4.33	-0.64	61.5
07/2006	5.18	4.12	-1.06	43.0
08/2006	4.95	4.19	-0.76	98.8
09/2006	5.19	4.78	-0.41	98.3
10/2006	5.13	4.85	-0.27	99.2
11/2006	4.54	4.40	-0.14	87.4
All	5.29	4.84	-0.45	90.5

**Table 3:** Monthly-mean 20m wind speeds (m/s) at Tower 06008. Time series graph of data is available in Figure 2 (p. 6).


Observed = mean of all available wind speed observations

Simulated = mean of simulated model output for times with observations

Bias = Simulated – Observed



## Observations




**Table 4:** Hourly-mean values of observed 20m wind speed at Tower 06008. Hours missing greater than 50% of the available observations are not plotted. Time series graphs are available in Figures 7 and 8 (p. 11 and 12).



Validation

Tower 06008

Western Wind and Solar Integration Study  
For National Renewable Energy Laboratory

**Table 5:** Hourly-mean values of simulated 20m wind speed at Tower 06008. Hours missing greater than 50% of the available observations are not plotted. All model values are computed only for times with valid observations. Time series plots are available in Figures 7 and 8 (p. 11 and 12).



Wind Speed (m/s)	N	NNE	NE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	All	
0 - 0.5	0.12	0.06	0.03	0.06	0.06	0.09	0.11	0.08	0.10	0.12	0.13	0.08	0.11	0.10	0.10	1.45	
0.5 - 1.5	0.30	0.28	0.22	0.31	0.32	0.33	0.49	0.44	0.61	0.60	0.67	0.45	0.52	0.41	0.36	0.24	6.54
1.5 - 2.5	0.44	0.53	0.42	0.45	0.53	0.41	0.78	0.80	0.98	1.13	1.00	0.77	0.68	0.51	0.50	0.50	10.43
2.5 - 3.5	0.71	0.73	0.61	0.76	0.60	0.81	0.94	1.08	1.56	1.72	1.16	1.10	1.03	0.66	0.68	0.51	14.66
3.5 - 4.5	0.78	0.87	1.05	0.91	0.86	0.61	1.10	1.42	1.38	1.48	1.00	0.83	0.98	0.95	0.71	0.71	15.65
4.5 - 5.5	0.90	0.63	0.79	0.62	0.51	0.62	1.26	1.26	1.00	0.96	0.50	0.45	1.13	1.06	0.89	0.90	13.48
5.5 - 6.5	0.52	0.52	0.50	0.36	0.40	0.58	1.17	0.87	0.56	0.60	0.31	0.17	0.79	1.16	0.97	0.90	10.36
6.5 - 7.5	0.42	0.44	0.32	0.17	0.15	0.35	0.66	0.45	0.40	0.28	0.14	0.27	0.63	0.96	0.83	0.68	7.14
7.5 - 8.5	0.41	0.35	0.21	0.12	0.07	0.20	0.49	0.39	0.27	0.14	0.05	0.12	0.48	0.70	0.83	0.68	5.52
8.5 - 9.5	0.26	0.21	0.12	0.05	0.04	0.14	0.36	0.32	0.15	0.10	0.08	0.11	0.29	0.52	0.67	0.58	3.99
9.5 - 10.5	0.34	0.12	0.06	0.04	0.00	0.04	0.17	0.20	0.05	0.02	0.07	0.09	0.23	0.53	0.52	0.40	2.89
10.5 - 11.5	0.20	0.06	0.04	0.05	0.03	0.03	0.11	0.15	0.03	0.04	0.11	0.05	0.14	0.40	0.48	0.44	2.35
11.5 - 12.5	0.08	0.00	0.01	0.03	0.00	0.01	0.04	0.02	0.02	0.02	0.04	0.06	0.23	0.46	0.27	1.30	
12.5 - 13.5	0.10	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.03	0.06	0.04	0.04	0.04	0.27	0.43	0.20	1.22
13.5 - 14.5	0.06	0.01	0.00	0.00	0.00	0.01	0.01	0.00	0.04	0.04	0.01	0.06	0.18	0.30	0.14	0.85	
14.5 - 15.5	0.01	0.02	0.00	0.00	0.01	0.00	0.01	0.01	0.00	0.02	0.04	0.02	0.04	0.08	0.16	0.08	0.49
15.5 - 16.5	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.02	0.00	0.05	0.16	0.21	0.04	0.53
16.5 - 17.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00	0.01	0.01	0.06	0.15	0.10	0.36
17.5 - 18.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.01	0.00	0.02	0.08	0.15	0.03	0.30
18.5 - 19.5	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.02	0.05	0.07	0.02	0.19
19.5 - 20.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.08	0.00	0.11
20.5 - 21.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.04	0.01	0.08
21.5 - 22.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.02	0.00	0.00	0.04
22.5 - 23.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.03	0.00	0.06
23.5 - 24.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.00	0.00	0.02
> 24.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

**Table 6:** Distribution of observed 20m wind speed by direction at Tower 06008. Histogram of data is available in Figure 3 (p. 7).



Wind Speed (m/s)	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	All
0 - 0.5	0.04	0.04	0.03	0.12	0.04	0.03	0.04	0.11	0.03	0.04	0.06	0.06	0.10	0.09	0.09	0.03	0.93
0.5 - 1.5	0.33	0.24	0.30	0.24	0.28	0.20	0.28	0.45	0.57	0.48	0.56	0.42	0.39	0.46	0.36	0.39	5.96
1.5 - 2.5	0.57	0.51	0.46	0.59	0.36	0.41	0.49	1.31	1.64	1.15	1.22	0.96	0.62	0.62	0.69	0.69	12.29
2.5 - 3.5	0.83	0.52	0.47	0.76	0.43	0.36	0.49	1.34	2.16	1.64	1.30	1.16	0.92	0.83	0.68	0.71	14.59
3.5 - 4.5	0.90	0.68	0.56	0.88	0.61	0.44	0.68	1.20	2.03	1.63	1.40	1.22	1.04	0.91	1.04	1.37	16.58
4.5 - 5.5	0.92	0.58	0.61	0.67	0.34	0.36	0.74	1.38	1.80	1.68	1.09	0.86	1.00	1.32	1.47	1.37	16.19
5.5 - 6.5	0.76	0.36	0.37	0.28	0.15	0.16	0.54	1.01	1.33	1.06	0.38	0.37	0.97	1.00	1.56	1.40	11.70
6.5 - 7.5	0.81	0.32	0.38	0.16	0.09	0.12	0.26	0.39	0.49	0.37	0.19	0.15	0.32	0.73	1.46	1.21	7.45
7.5 - 8.5	0.51	0.33	0.18	0.12	0.07	0.04	0.04	0.32	0.34	0.15	0.04	0.05	0.23	0.50	0.86	1.07	4.86
8.5 - 9.5	0.41	0.14	0.12	0.06	0.03	0.03	0.06	0.20	0.16	0.10	0.03	0.09	0.09	0.33	0.74	0.84	3.41
9.5 - 10.5	0.22	0.03	0.04	0.04	0.02	0.00	0.05	0.04	0.04	0.05	0.07	0.01	0.04	0.17	0.60	0.63	2.04
10.5 - 11.5	0.19	0.04	0.08	0.03	0.00	0.00	0.03	0.04	0.01	0.03	0.01	0.01	0.04	0.07	0.42	0.58	1.56
11.5 - 12.5	0.11	0.04	0.00	0.04	0.00	0.00	0.00	0.02	0.00	0.02	0.03	0.01	0.03	0.05	0.24	0.27	0.84
12.5 - 13.5	0.08	0.04	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.16	0.14	0.53
13.5 - 14.5	0.02	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.00	0.07	0.19	0.33
14.5 - 15.5	0.04	0.02	0.03	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.05	0.17	0.33
15.5 - 16.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.05	0.14	0.20
16.5 - 17.5	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.01	0.02	0.09	0.14
17.5 - 18.5	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.03
18.5 - 19.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.02	0.02	
19.5 - 20.5	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.02
20.5 - 21.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
21.5 - 22.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
22.5 - 23.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
23.5 - 24.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
> 24.5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

**Table 7:** Distribution of simulated 20m wind speed by direction at Tower 06008. All model values are computed only for times with valid observations.  
Histogram of data is available in Figure 3 (p. 7).

Sector	Mean Speed(m/s)	Weibull Scale(A)	Weibull Shape(k)	Frequency(%)
N	5.60	6.30	1.78	5.65
NNE	4.80	5.42	1.97	4.84
NE	4.63	5.22	2.26	4.39
ENE	4.14	4.67	1.97	3.94
E	3.91	4.41	1.96	3.59
ESE	4.44	5.02	2.00	4.22
SE	4.95	5.58	2.06	7.68
SSE	4.76	5.37	2.01	7.53
S	4.07	4.59	1.97	7.12
SSW	4.04	4.52	1.68	7.35
SW	3.94	4.35	1.44	5.40
WSW	4.02	4.48	1.59	4.66
W	5.27	5.90	1.68	7.34
WNW	7.03	7.89	1.76	9.14
NW	8.00	8.98	1.74	9.64
NNW	6.91	7.79	1.90	7.51
ALL	5.29	5.91	1.63	100.0

**Table 8:** Observed 20m mean wind speed, Weibull parameters, and frequency at Tower 06008. Blank values correspond to times with less than 10 data points. Wind rose of data is available in Figure 4 (p. 8).

Sector	Mean Speed(m/s)	Weibull Scale(A)	Weibull Shape(k)	Frequency(%)
N	5.61	6.33	1.96	6.74
NNE	4.84	5.45	1.90	3.88
NE	4.81	5.41	1.85	3.68
ENE	4.01	4.52	1.93	3.98
E	3.73	4.20	1.92	2.44
ESE	3.74	4.22	2.06	2.14
SE	4.32	4.88	2.18	3.71
SSE	4.24	4.79	2.10	7.80
S	4.10	4.63	2.32	10.60
SSW	4.14	4.68	2.33	8.40
SW	3.66	4.13	2.02	6.39
WSW	3.77	4.25	2.02	5.40
W	4.50	5.08	1.96	5.85
WNW	5.11	5.76	2.05	7.14
NW	6.34	7.15	2.18	10.56
NNW	6.74	7.61	2.04	11.30
ALL	4.84	5.45	1.87	100.0

**Table 9:** Simulated 20m mean wind speed, Weibull parameters, and frequency at Tower 06008. All model values are computed only for times with valid observations; blank values correspond to times with less than 10 data points. Wind rose of data is available in Figure 4 (p. 8).